

YORK RAKES

A division of YORK MODERN CORPORATION

P.O. Box 488, Unadilla, N.Y. 13849, Phone: 607-369-7111 or 800-643-YORK

Fax: 607-369-2625 Web: www.yorkmodern.com E-Mail: sales@yorkmodern.com



5' — PTO - Power Rake



- **Durable Rake Teeth** - Pointed carbide studs **Silver Brazed** to the stud base for superior connection. Pointed teeth penetrate better.
- **Rugged Driveline** – Gearbox is rated for 45 HP, nearly double other units on the market. Slip clutch requires NO BREAK IN or MAINTENANCE.
- **Quick Hitch Compatible Three-Point Hitch Frame** - Triangular design fortifies the pivot point for a stronger connection
- **Storage Stand** - Eases of connecting and disconnecting the unit from the tractor.
- **Lifting Ring** – Makes moving the unit safer and easier when it's not on the tractor.
- **Simple Design** - Makes the unit reliable and easier to maintain.
- **Roller Bearings** -Triple sealed, permanently greased ball bearings.
- **Drive Chain** - Double 50-roller chain in an oil bath housing. Chain tension is self-adjusting.
- **Hydraulic Angle** - Maximum of 15 degrees right or left. The cylinder is a standard rugged agricultural tie rod type, easily repaired or replaced.
- **Adjustable Urethane Barrier** – Regulates how much material you process and how fine a job you do.
- **End Boots** – Like other York Rakes, end boots increase the carrying capacity of the unit, there by allowing it to process more material. York's end boots have hard faced leading edges for increase wear.
- **Caster Wheels** – Use urethane filled, flat free, turf tires that are 16 x 6.5-8.
- **Warranty** – One year with the first 90 days covered 100%.
- **5' – 750 lbs.**
- **Quality, Service, Delivery** – York hallmarks for over 80 years.

SL-YPR5