



Models MT2, MR2 & MR3

Light / Medium Duty Landscape Rakes.

BASIC Line



Model	003264	003265	003266	003274	003275	003276	003376	003377	003378
Weight	108#	162#	175#	120#	132#	149#	233#	255#	280#
Max. Raking Width	4'	5'	6'	4'	5'	6'	6'	7'	8'
Min. Raking Width	40"	53"	56"	34"	44"	50"	56"	65"	74"
Working Pos. (Fwd.)	3	5							
Working Pos. (Rev.)	N/A			3					
Vertical Adjustment	Manual Lever.			N/A					
HP Rating	Max. 20 HP						Max. 30 HP		
Tooth Size	1/4" x 1" x 22", Heat Treated Alloy Steel.						5/16" x 1" x 28", Heat Treated Alloy Steel.		
Tooth Spacing	1"						1"		
Rakeheads	Mild Steel								
Hitch	Pin Type			Category 0 or 1, 3 Pt. Hitch.			Category 1, 3 Pt. Hitch		
Tires/Bearings	10x2.75 Semi-pneumatic/Sintered.	12x3 Semi-pneumatic/Sintered		N/A					
Caster Wheels	N/A			Optional, 10x2.75 Semi-pneumatic/Sintered, 35# per Pair.			Optional, 12x3 Semi-pneumatic/Sintered, 59# per Pair.		

A division of YORK MODERN CORPORATION • UNADILLA, NY 13849 • 800-643-YORK (9675) or 607-369-7111 • Fax: 607-369-2625

E-mail: sales@yorkmodern.com Web: www.yorkmodern.com

Form SL-MT2MR2MR3S09 (Rev. 6/2009)

Specifications subject to change without notice.

Printed in USA