

# YORK RAKE

## Model TA1 & TA2



Handle a Variety of Jobs...Faster, Better!  
Add More Workability to Riding Tractors, ATVs and UTVs.

1-7/8" Ball Hitch Compatible!



Model	001214	001214B	002214	002214B	002215	002215B	002216	002216B
Weight	121#	121#	203#	203#	217#	217#	231#	231#
Max. Raking Width	4'	4'	4'	4'	5'	5'	6'	6'
Min. Raking Width	40"	40"	40"	40"	43"	43"	56"	56"
Angling	3 Pos. Man. Angle.		5 Position Manual Angle.					
Vertical Adjustment	Manual Lever. Optional Electric/Hydraulic Cylinder Available.							
HP Rating	10 HP.		Over 10 HP.					
Tooth Size	1/4" x 1" x 22", Heat Treated Alloy Steel.							
Tooth Spacing	1"							
No. of Teeth	24	24	24	24	30	30	36	36
Rake Heads	Spring Steel							
Hitch **	Pin	Ball, 1-7/8"	Pin	Ball, 1-7/8"	Pin	Ball, 1-7/8"	Pin	Ball, 1-7/8"
Tires/Bearings	8.25 x 2.75 Semi-pneumatic/Roller.		16 x 6.5-8 2 Ply Tubeless-pneumatic/Roller.					
Grader Blade	Optional, 4' - 36#				Optional, 5' - 42#		Optional, 6' - 47#	

\*\* ATV/UTV Compatible.